

SAFETY DATA SHEET

SECTION 1 PRODUCT INDENTIFICATION

Product Name:	Acrylic Liquid
Chemical Name:	Ethyl Methacrylate Solution
Product Use:	PROFESSIONAL USE ONLY
Manufacturer's Name:	Glittergasm Australia
Manufacturer's Address:	4 Queens Parade Brighton QLD 4017
Phone:	0490 387 854
Emergency Phone Number:	Poisons Information Australia: 13 11 26

SECTION 2 HAZARD INDENTIFICATION

Hazard Identificaton:

This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). Flammable Liquid, Skin				
classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). Flammable Liquid, Skin				
classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). Flammable Liquid, Skin				
Corrosion/Irritation, Skin Sensitizer, Carcenogenicity, Specific Target Orgon Toxicity - Single Exposure				
. AVOID SKIN CONTACT DUE TO IRRITATION AND CHEMICAL BURN POTENTIAL. MAY CAUSE EYE				
IRRITATION OR DAMAGE. Hazard Statements (H): H225 - Highly flammable liquid and vapor, H315 -				
Causes skin irritation, H317 - May cause an allergic skin reaction, H319 - Causes serious eye				
irritation, H351 - Suspected of causing cancer. Precautionary Statements (P): P201 - Obtain special	\mathbf{A}			
instructions before use, P202 - Do not handle until all safety precautions have been read and				
understood, P210 - Keep away from heat/sparks/open flames/hot surfaces - No smoking, P233 -	~			
Keep container tightly closed, P-240 - Ground and bond container and recieving equipment, P241 -	× ·			
Use only nonsparking tools, P243 - Take precautionary measures against static discharge, P261 -				
Avoid breathing dust/fumes/gas/mist/vapors/spray, P264 - Wash hands and exposed skin				
thoroughly after handling, P271 Use only outdoors or in well ventilated area, P272 - Contaimated				
work clothing should not be allowed out of the work place, P280 - Wear protective gloves,	X			
protective clothing, eye protection, face protection, P281 - Use personal protective equipment as				
required, P312 - Call a POISON CENTER or doctor/physician if you feel unwell, P321 - Specific				
treatment (see Section 4 in this document), P362 - Take off contaminated clothing and wash before				
reuse, P363 - Wash contaminated clothing before reuse, P302 & P352 - IF ON SKIN: Wash with soap	~			
and water, P303, P361 & P353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated				
clothing. Rinse skin with water/shower, P304 & P340 - IF INHALED: Remove victim to fresh air and				
keep at rest in a position comfortable for breathing, IF IN EYEES: Rinse continually with water for				
several minutes. Remove contact lenses if present and easy to do - continue rinsing, P308 & P313 -				
Get medical advise/attention, P370 & P378 - In case of fire: Use CO2 for extinguishing, P405 - Store				
locked-up, P403 & P223 - Store in a well ventialated area				
Routes of Entry: Inhalation: Yes Absorption: Yes	Ingestion: Yes			
Effects of Exposure:				
Swallowing this material may be harmful or fatal. Symptoms may include	severe stomach and			
INGESTION: intestinal irritation, abdominal pain, and vomiting of blood. Swallowing this material may cause				
burns and destroy tissue in the mouth, throat and digestive				
Can cause permanent eye injury. Symptoms include stinging, tearing, redr	ness and swelling of the			
EYES & SKIN: eyes. Can injure the cornea and cause blindness. Can cause permanent sk	in damage. Symptoms may			
include redness, burning and swelling of the skin, burns and other skin da	mage.			
Vapors of this material may be irritating to the nasal passage and lungs an	nd in severe cases cause			
INHALATION: burning of the tissue.				

٦



Symptoms of	Symptoms of overexposure are irritation of the tissue, nausea, dizziness, and shortness of breath,
Overexposure:	swelling of the eyes and skin.
Acute Health Effects:	Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. LD50: 1650 mg/kg Species: Rat
Chronic Health Effects:	None
Target Organs:	Eyes, skin, lungs and respiratory tract

SECTION 3 COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%
	97-63-2	NA	202-597-5	70-80
Ethyl Methacrylate	Skin Corrosion/Irritation 2 (H	1315), Eye Damage/Irritati	on 2A (H319), Skin Sensiti	zer 1 (H317), Specific
	Target Organ, Toxicity - Singl	e Exposure 3 (H335)		
Hydrowypropyl Mothacrylata	27813-02-1	NA	248-666-3	5-10
Hydroxypropyl Methacrylate	Eye Damage/Irritation 2A (H	319), Skin Sensitizer 1 (H3	17)	
	1830-78-0	NA	217-338-4	5-10
Glyceryl Dimethacrylate	Skin Corrosion/Irritation 2 (H	1315), Eye Damage/Irritati	on 2A (H319), Skin Sensiti	zer 1 (H317), Specific
Target Organ, Toxicity - Single Exposure 3 (H335)				
Triethyleneglycol	109-16-0	NA	203-652-6	1-5
Dimethacrylate	Skin Sensitizer 1 (H317)			
	99-97-8	NA	202-805-4	0-1
Dimethyltolylamine	Oral Toxicity Acute Tox. 3 (H	301), Dermal Toxicity Acu	te Tox 3 (H311), Inhalalati	on Toxicity Acute Tox.
Dimethyltolylamine	3 (H331), Carcenogenicity 2 (H351), Specific Target Organ, Toxicity - Repeated, Exposure 2 (H373),			
	Aquatic Toxicity C3 (H412)			
CI 60725 (Violet #2)	81-48-1	NA	201-353-5	≤0.1
Ci 60725 (Violet #2)				
** Due to trade secret information, more detailed concentrations of the ingredients cannot be provided.				

SECTION 4 FIRST AID MEASURES

First Aid:

INGESTION:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
EYES & SKIN:	If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soak and waster. Remove all contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
INHALATION:	Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

Medical Conditions	Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin)
Aggravated by	
Exposure:	

Notes to Physician:		Target Organs:		
, , ,	This product contains N,N-Dimethyl-p-toluidine at a very low concentration and does not meet the criteria for reporting in section 3		Skin	Lungs



SECTION 5 FIREFIGHTING MEASURES

Flashpoint & Method: 19 °C (66 °F) Closed Cup			
Autoignition Temperature: NA			
Flammability Limits:		Lower Explosive Limit (LEL): NA	Upper Explosive Limit (UEL): NA
Fire & Explosion Hazards:	This product is flammable. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)		may ignite and decompose to form
Extinguishing Methods:		Water, Foam, CO2, Dry Chemical	
Fire Fighting Procedures:	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other enviormentally sensitive reas. If necessary, rinse contaminated equipment with soapy water before returning to service		

SECTION 6 ACCIDENTAL RELEASE MEASURES

Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Remove spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entery to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Remove spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container spill with inert material (e.g., sand or earth). Remove spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies
---------	--

SECTION 7 HANDLING AND STORAGE INFOMATION

Work & Hygiene Practices:	Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.
Storage & Handling:	Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devises. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!
Special Precautions:	Do not store where temperatures can exceed 50 °C (122 °F)



SECTION 8 EXPOSURE CONTROLS & PERSONAL PROTECTION

Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontaimination equipment is available (e.g., sink, safety shower, eye wash station)	
Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Candaian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia	
Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants	
Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or imprevious gloves	
Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water	

SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

Density:	1.17
Boiling Point:	117 C
Melting Point:	NA
Evaporation Rate:	NA
Vapor Pressure:	NA
Appearance & Colour:	Clear to violet liquid
Odor Threashold:	NE
Solubility:	Soluble
pH:	NA
Viscosity:	approximately 25 cps
Flash Point:	19 °C (66 °F) calculated
Other Information:	NA

SECTION 10 STABILITY & REACTIVITY

Stability:	Relatively stable under ambient conditions when stored properly.	
Hazardous Decomposition	If exposed to extremely high temperatures, products of thermal decomposition may include irritating	
Products:	vapors and toxic gases (e.g., oxides of carbon and nitrogen).	
Hazardous Polymerization:	May occur.	
Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatable chemicals, strong light sources, sparks and flame.	
Incompatable Substances:	Strong oxidizers, peroxides, strong acids or alkalis.	



SECTION 11 TOXICOLOGICAL INFORMATION

Toxicity Data:	99-97-8: Dimethyltolylamine Oral: 1650 mg/kg (Rat), Dermal: 500 mg/kg (Rat), Inhalation:
	1400 mg/m3 (Rat) - conducted by the manufacutrer of Dimethyltolylamine
Acute Toxicity:	Moderate irritation to eyes near affected areas. Additionally, high concentrations of
	vapors can cause drowsiness, dizziness, headaches and nausea. LD50: 1650 mg/kg
	Species: Rat
Chronic Toxicity:	None
Suspected Carcinogen:	The ingredients of this product are not listed as carcinogens by the National Toxicology
	Program and have not been evaluated by the Internail Agency for Research on Cancer or
	the American Conference of Government Industrial Hygenists. Dimethyltolylamine is a suspected
Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.
Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
Teratogenicity:	This products is not reported to cause teratogenic effects in humans.
Irritancy of Product: Effects of Exposure:	
INGESTION:	Swallowing this material may be harmful or fatal. Symptoms may include severe stomach
	and intestinal irritation, abdominal pain, and vomiting of blood. Swallowing this material
	may cause burns and destroy tissue in the mouth, throat and digestive
EYES & SKIN:	Can cause permanent eye injury. Symptoms include stinging, tearing, redness and
	swelling of the eyes. Can injure the cornea and cause blindness. Can cause permanent
	skin damage. Symptoms may include redness, burning and swelling of the skin, burns and
	other skin damage.
INHALATION:	Vapors of this material may be irritating to the nasal passage and lungs and in severe
	cases cause burning of the tissue.
Biological Exposure Indicies:	NE
Physician Recommendations:	Treat symptomatically

SECTION 12 ECOLOGIAL INFORMATION

Environmental Stability:	This product will slowly evaporate from soil. Components of this product will slowly decompose into organic compounds. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegredation.
Effects on Plants & Animals:	There is no specific data available for this product on plant life.
Effects on Aquatic Life:	There is no specific data available for this product on aquatic life.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal:	Dispose in accordance with local, state and Federal waste laws.
Special Considerations:	This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations



SECTION 14 TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.

49 CFR (GRD):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020 UN2277, Ethyl
	Methacrylate, Stabilized, Solution, 8, II, LTD QTY (IP VOL \leq 1.0 L)
IATA (AIR):	ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) Passenger Aircraft: UN2277, Ethyl
	Methacrylate, Stabilized, Solution, 8, II, LTD QTY (IP VOL \leq 1.0 L) Cargo Aircraft: UN1760,
	Corrosive Liquids N.O.S., 8, III, (IP VOL ≤ 30.0 L)
IMDG (OCN):	UN1760, Corrosive Liquids N.O.S., 8, II, (IP VOL ≤ 10.0 L)
TDGR (Canadian GND):	MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR
	"QUANT LTEE" (IP VOL ≤ 1.0 L) UN2277, Ethyl Methacrylate, Stabilized, Solution, 8, II, LTD
	QTY (IP VOL \leq 1.0 L)
ADR/RID (EU):	UN2277, Ethyl Methacrylate, Stabilized, Solution, 8, II, LTD QTY (IP VOL \leq 1.0 L)
MEXICO (SCT):	UN2277, Ethyl Methacrylate, Stabilized, Solution, 8, II, LTD QTY (IP VOL \leq 1.0 L)
ADGR (AUS):	UN2277, Ethyl Methacrylate, Stabilized, Solution, 8, II, LTD QTY (IP VOL \leq 1.0 L)

SECTION 15 REGULATORY INFORMATION

SARA Reporting:	NA
SARA Threshold Planning Quantity:	NA
TSCA Inventory Status:	All components of this product are listed in the TSCA Inventory or are exempt
CERCLA Reportable Quantity (RQ):	NA
Other Federal Requirements:	This products complies with the appropriate sections of the Food and Drug
	Administration's 21 CFR subchapter G (Cosmetics).
Other Canadian Regulations:	This product has been classified according to the hazard criteria
	of the CPR and the SDS contains all of the information required (
	by the CPR. The components of this product are listed on the
	DSL/NDSL. None of the components of this product are on the
	Priorities Substances List
State Regulatory Information:	No other ingredients in this product, present in a concentration of 1.0% or greater, are
	listed on any of the following state criteria lists: California Proposition 65 (CA), Delaware
	Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts
	Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota
	Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ), new Yord Hazardous
	Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible
	Exposures List (WA), Wisconsin Hazardous Substances List (WI)
67/548/EEC (European Union), Australian	The primary cononent of this product is listed in Annex 1 of EU
NOHSC:2011 (2003), and GHS	Directive 67/548/EEC. 99-97-8 Dimethyltolylamine: 0.1 - 1.0%
Requirements:	Carcinogen Risk Phrases (R): See section 2.1



SECTION 16 OTHER INFORMATION

	WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume,
Other Information:	gas, mist, vapors, spray. Wear potective gloves and eye/face protection. IF ON SKIN - Wash with soap and
	water. IF IN EYES - Rinse continuously with water for several minutes.
	Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash
	occurs - get medical advice/attention. Do not take internally. Keep away from heat and open
	flame. KEEP OUT OF THE REACH OF CHILDREN.
Terms & Definitions:	Please see last page of this SDS.
	This Safety Data Sheet (SDS) is offered persuant to OSHA's Hazard Communication Standard, 29 CFR
	§1910.1200. Other government regulations must be reviewed for applicability to this product. To the best
	of Glittergasm knowledge, the information contained herein is reliable and accurate as of the date it was
Disclaimer:	prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any
	type, either expressed or implied, are provided. The information contained herein relates only to the
	specific product(s). If this product(s) is combined with other materials, all component properties must be
	considered. Data may be changed from time to time. Be sure to consult the latest edition.
Prepared for and by:	
Glittergasm Australia	
4 Queens Parade	the source of the first the
Brighton QLD 4017	
PH: 0490 387 854	littérgasm
11.0430 307 034	

Page **7** of **8**



DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following: GENERAL INFORMATION:

CAS No. Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:	
ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health

FIRST AID MEASURES:


CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard	HEALTH
1	Slight Hazard	FLAMMABILITY
2	Moderate Hazard	PHYSICAL HAZARDS
3	Severe Hazard	PERSONAL PROTECTION
4	Extreme Hazard	

PERSONAL PROTECTION RATINGS:



OTHER STANDARD ABBREVIATIONS:

Full Face Respirator

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

Respirato

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:		
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition	
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source	
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source	

HAZARD RATINGS:

0	0 Minimal Hazard					
1	Slight Hazard					
2	Moderate Hazard					
3	Severe Hazard					
4	Extreme Hazard					
ACD	Acidic					
ALK	Alkaline					
COR	Corrosive					
₩	Use No Water					
OX	Oxidizer					
TREFOIL	Radioactive					



TOXICOLOGICAL INFORMATION:

LD ₅₀	LD50 Lethal Dose (solids & liquids) which kills 50% of the exposed animals						
	S						
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal						
ppm	Concentration expressed in parts of material per million parts						
TD ₁₀	Lowest dose to cause a symptom						
TCLo	Lowest concentration to cause a symptom						
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects						
TC, TC ₀ , LC ₁₀ , & LC ₀							
IARC	International Agency for Research on Cancer						
NTP	National Toxicology Program						
RTECS	Registry of Toxic Effects of Chemical Substances						
BCF	Bioconcentration Factor						
TLm	Median threshold limit						
log Kow or log Koc	Coefficient of Oil/Water Distribution						

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	۲	٨	$\textcircled{\begin{subarray}{c} \end{subarray}}$	1	۲		R
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		*	¥		&	×	×
с	E	F	Ν	0	т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

	٨	٩	\diamondsuit			(!)		
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment