



SAFETY DATA SHEET

SECTION 1 PRODUCT IDENTIFICATION

Product Name: Acid Primer
 Chemical Name: Methacrylic Acid Solution
 Product Use: PROFESSIONAL USE ONLY
 Manufacturer's Name: Glittergasm Australia
 Manufacturer's Address: 4 Queens Parade Brighton QLD 4017
 Phone: 0490 387 854
 Emergency Phone Number: Poisons Information Australia: 13 11 26

SECTION 2 HAZARD IDENTIFICATION

Hazard Identification:				
<p>This product is classified as a HAZARDOUS SUBSTANCE and as a DANGEROUS GOOD according to the classification criteria of NOHSC: 1008 (2004) and ADG Code (Australia). WARNING! MAY CAUSE PERMANENT SKIN DAMAGE. AVOID SKIN CONTACT DUE TO IRRITATION AND CHEMICAL BURN POTENTIAL. MAY CAUSE EYE IRRITATION OR DAMAGE. Hazard Statements (H): H227 -Combustible liquid and vapor , H302 - Harmful if swallowed, H-312 - Harmful in contact with skin , H332 - Harmful if inhaled , H314 - Causes severe skin burns and eye damage. Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces - No Smoking. P223 - Keep container tightly closed. P261 - Avoid breathing fumes/gas/vapors/spray. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves. P302 + P352 - IF ON SKIN - wash with soap and warm water. P305 + P351 + P338 - IF IN EYES - Rinse continually with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. P333 + P313 - If skin reaction or a rash occurs, get medical attention. P337 + P313 - If eye irritation persists, P321 - for specific first aid treatment (see section 4 of this Safety Data Sheet). P363 - Wash contaminated clothing before reuse. P501 - Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF).</p>				
Routes of Entry:		Inhalation: Yes	Absorption: Yes	Ingestion: Yes
Effects of Exposure:				
INGESTION:	Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation, abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat and digestive			
EYES & SKIN:	Can cause permanent eye injury. Symptoms include stinging, tearing, redness and swelling of the eyes. Can injure the cornea and cause blindness. Can cause permanent skin damage. Symptoms may include redness, burning and swelling of the skin, burns and other skin damage.			
INHALATION:	Vapors of this material may be irritating to the nasal passage and lungs and in severe cases cause burning of the tissue.			
Symptoms of Overexposure:	Symptoms of overexposure are irritation of the tissue, nausea, dizziness, and shortness of breath, swelling of the eyes and skin.			
Acute Health Effects:	Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. LD50: 1060 mg/kg Species: Rat			
Chronic Health Effects:	None			
Target Organs:	Eyes, skin, lungs and respiratory tract			



SECTION 3 COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS INAIR (mg/m3)								
					ACGIH		NOHSC			OSHA			OTHER
					ppm		ppm			ppm			
					TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
Glacial Methacrylic Acid	79-41-4	NA	201-204-4	<99.5	20	NA	20	NA	NF	NA	NA	NA	
Tocopheryl Acetate (Vitamin E)	58-95-7	GP820000	200-405-4	<0.1	NA	NA	NF	NF	NF	NA	NA	NA	

SECTION 4 FIRST AID MEASURES

First Aid:

INGESTION:	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
EYES & SKIN:	If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Open and close eyelid(s) to ensure thorough irrigation. Seek immediate medical attention. If problem persists, seek immediate medical attention. If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water followed by a thorough washing of the affected area with plenty of soap and water. Remove all contaminated clothing including footwear and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
INHALATION:	Remove victim to fresh air at once. If breathing stops, perform artificial respiration. Seek immediate medical attention.

Medical Conditions Aggravated by Exposure:	Pre-existing dermatitis, other skin conditions and disorders of the target organs (eyes, skin)	Target Organs:	Eyes	Skin	Lungs
--	--	----------------	------	------	-------

SECTION 5 FIREFIGHTING MEASURES

Flashpoint & Method:	77.22 °C (171 °F) Closed Cup				
Autoignition Temperature:	68 °C (154 °F)				
Flammability Limits:	Lower Explosive Limit (LEL): NA		Upper Explosive Limit (UEL): NA		
Fire & Explosion Hazards:	This product is combustible. When involved in a fire, this product may ignite and decompose to form toxic gases (e.g., CO, CO2 and Nox)				
Extinguishing Methods:	Water, Foam, CO2, Dry Chemical				
Fire Fighting Procedures:	First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH approved, self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before return to service.				





SECTION 6 ACCIDENTAL RELEASE MEASURES

Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. For small spills (e.g., , 1 gallon [3.785 liters]) wear appropriate personal protective equipment (e.g., goggles & gloves). Maximize ventilation (open doors and windows). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. For large spills (e.g., > 1 gallon [3.785 liters]) deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Expose spilled material to UV light source for 2-5 minutes. Lift cured material from substrate and repeat until very little residue remains. Remove remaining spilled material with absorbent material and place into appropriate closed container(s). Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with warm, soapy water. Remove any contaminated clothing and wash before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
---------	---

SECTION 7 HANDLING AND STORAGE INFORMATION

Work & Hygiene Practices:	Avoid prolonged contact with this material. Avoid breathing the vapors generated by this product. Use in a well ventilated location (e.g., local exhaust ventilation, fans). Wash exposed skin thoroughly with plenty of soap and water after using this product. If necessary, use a moisturizer after washing. Do not eat, drink or smoke while handling this product.
Storage & Handling:	Use and store in a cool, dry, well ventilated location. Keep away from excessive heat. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care. As a precaution against exposure to the eyes, nose, throat and face, this product should not be stored higher than waist level. KEEP AWAY FROM CHILDREN AT ALL TIMES!
Special Precautions:	Do not store where temperatures can exceed 50 °C (122 °F)

SECTION 8 EXPOSURE CONTROLS & PERSONAL PROTECTION

Ventilation & Engineering Controls:	Use with adequate ventilation (e.g., local exhaust ventilation, fans). Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye wash station).	
Respiratory Protection:	No special respiratory protections is required under typical circumstances of use or handling. In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR § 1910.134, application U.S. State regulations or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC Member States or Australia.	
Eye Protection:	Wear protective eyewear (e.g., safety glasses with side shields) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants.	
Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., >1 gallon [3.785 liters]), wear nitrile or impervious gloves.	
Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., . 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.	



SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

Density:	1.015
Boiling Point:	163 °C (325 °F)
Melting Point:	16 °C (61 °F)
Evaporation Rate:	<1 n-Butyl Acetate
Vapor Pressure:	0.131 kPa @ 25°C
Appearance & Colour:	Clear liquid
Odor Threshold:	NE
Solubility:	Soluble
pH:	NA
Viscosity:	Approximately 25 cps
Flash Point:	77 °C (171 °F) calculated
Other Information:	NA

SECTION 10 STABILITY & REACTIVITY

Stability:	Relatively stable under ambient conditions when stored properly.
Hazardous Decomposition Products:	If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon and nitrogen).
Hazardous Polymerization:	Will not occur.
Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks and flame.
Incompatible Substances:	Strong oxidizers, peroxides, strong acids or alkalis.



SECTION 11 TOXICOLOGICAL INFORMATION

Toxicity Data:	Performed by the manufacturer of the methacrylic acid Acute Oral Toxicity: LD50: 1060 mg/kg Species: Rat Acute Inhalation Toxicity: LD50: 7.1 mg/l Exposure time: 4 hrs Species: Rat Acute Dermal Toxicity: LD50: 500 mg/kg Species: Rabbit
Acute Toxicity:	Moderate irritation to eyes near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea. LD50: 1060 mg/kg Species: Rat
Chronic Toxicity:	None
Suspected Carcinogen:	The ingredients of this product are not listed as carcinogens by the National Toxicology Program and have not been evaluated by the Internal Agency for Research on Cancer or the American Conference of Government Industrial Hygienists.
Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.
Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
Teratogenicity:	This products is not reported to cause teratogenic effects in humans.
Irritancy of Product: Effects of Exposure:	
INGESTION:	This products is not reported to cause teratogenic effects in humans
EYES & SKIN:	Can cause permanent eye injury. Symptoms include stinging, tearing, redness and swelling of the eyes. Can injure the cornea and cause blindness. Can cause permanent skin damage. Symptoms may include redness, burning and swelling of the skin, burns and other skin damage.
INHALATION:	Vapors of this material may be irritating to the nasal passage and lungs and in severe cases cause burning of the tissue.
Biological Exposure Indices:	NE
Physician Recommendations:	Treat symptomatically

SECTION 12 ECOLOGIAL INFORMATION

Environmental Stability:	This product will slowly evaporate from soil. Components of this product will slowly decompose into organic compounds. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization and biodegradation.
Effects on Plants & Animals:	There is no specific data available for this product on plant life.
Effects on Aquatic Life:	There is no specific data available for this product on aquatic life.

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Disposal:	Dispose in accordance with local, state and Federal waste laws.
Special Considerations:	This material becomes an inert plastic upon prolonged exposure to sources of UV light and sunlight. Disposal of inert plastics is safer for the environment and is more easily handled for disposal according to local, state and Federal regulations





SECTION 14 TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG, SCT, ADR and the CTDGR.


49 CFR (GRD):	CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L) - UNTIL 12/31/2020 UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 1.0 L)
IATA (AIR):	Passenger Aircraft: UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 0.5 L) Cargo Aircraft: UN1760, Corrosive Liquids (Methacrylic Liquid), 8, III, (IP VOL ≤ 30.0 L)
IMDG (OCN):	UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, (IP VOL ≤ 10.0 L)
TDGR (Canadian GND):	MARK PACKAGE "LIMITED QUANTITY" OR "QUANTITE LIMUTEE" OR "LTD QTY" OR "QUANT LTEE" (IP VOL ≤ 0.5 L) UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 0.5 L)
ADR/RID (EU):	UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 0.5 L)
MEXICO (SCT):	UN1760, Corrosivo Liquidos (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 0.5 L)
ADGR (AUS):	UN1760, Corrosive Liquids (Methacrylic Liquid), 8, II, LTD QTY (IP VOL ≤ 0.5 L)

SECTION 15 REGULATORY INFORMATION

SARA Reporting:	NA	
SARA Threshold Planning Quantity:	NA	
TSCA Inventory Status:	All components of this product are listed in the TSCA Inventory or are exempt	
CERCLA Reportable Quantity (RQ):	NA	
Other Federal Requirements:	This products complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics).	
Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are on the Priorities Substances List.	
State Regulatory Information:	No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances list, (MN), New Jersey Right-to-Know List (NJ), new York Hazardous Substances List (NY), Pennsylvania Right-to-Know list (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI)	
67/548/EEC (European Union), Australian NOHSC:2011 (2003), and GHS Requirements:	The primary cononent of this product is listed in Annex 1 of EU Directive 67/548/EEC. Methacrylic Acid: Harmful (Xi). Risk Phrases (R): See section 2	



SECTION 16 OTHER INFORMATION

Other Information:	WARNING! MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES EYE IRRITATION. Avoid breathing fume, gas, mist, vapors, spray. Wear protective gloves and eye/face protection. IF ON SKIN - Wash with soap and water. IF IN EYES - Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing. If skin irritation or a rash occurs - get medical advice/attention. Do not take internally. Keep away from heat and open flame. KEEP OUT OF THE REACH OF CHILDREN
Terms & Definitions:	Please see last page of this SDS.
Disclaimer:	This Safety Data Sheet (SDS) is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Glittergasm's knowledge, the information contained herein is reliable and accurate as of the date it was prepared; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
Prepared for and by: Glittergasm Australia 4 Queens Parade Brighton QLD 4017 PH: 0490 387 854	



DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
---------	----------------------------------

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
TLV	Threshold Limit Value
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
IDLH	Immediately Dangerous to Life and Health


FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard



PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.



OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus


NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:

Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₀₁	Lowest dose to cause a symptom
TCLO	Lowest concentration to cause a symptom
TD ₀₁ , LD ₀₁ , & LD ₀₁ or TC, TC ₀₁ , LC ₀₁ , & LC ₀₁	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

C	E	F	N	O	T	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment